



Round Diffuser - 4" (10.1 cm) & 6" (15.2 cm) plastic adjustable diffuser grills designed for suspended ceiling applications



TFG4, TFG6, TFGX4, TFGX6

Model No.	A	B	use flex duct
TFG4	3 7/8"	5 7/8"	4" dia.
TFG6	5 7/8"	7 7/8"	6" dia.
TFGX4	3 7/8"	5 7/8"	4" dia.
TFGX6	5 7/8"	7 7/8"	6" dia.



Model No.	Face Velocity FPM									
		300	400	500	600	700	800	900	1000	
TFG4, TFGX4	CFM	13	18	22	26	31	35	40	44	
	PL*	0.02	0.02	0.03	0.03	0.04	0.05	0.05	0.06	
TFG6, TFGX6	CFM	39	52	66	79	92	105	118	131	
	PL*	0.00	0.00	0.01	0.02	0.03	0.04	0.06	0.07	

*PL is total pressure loss (in inches W C) at maximum opening.

Model No.	Description	Color
TFG4	4" Diffuser	White
TFG6	6" Diffuser	White
TFGX4	4" Diffuser in a bag	White
TFGX6	6" Diffuser in a bag	White

Performance Data

for round plastic adjustable diffusers

Diffuser

- Calcium filled Polypropylene
- Melting point: 325°F+ (163°C approx.)

Note

- we recommend using Supurr-Flex® pure aluminum flexible metallic duct

Technical Data

- each 4" (10.1cm) diameter installation is designed to handle areas up to 60 sq. ft. (5.5 sq. m)
- each 6" (15.2cm) diameter installation is designed to handle areas up to 150 sq. ft. (14 sq. m)

General Information

- ideal for suspended ceilings
- designed for suspended ceiling exhaust of heating and cooling applications
- easy to adjust and install
- unique locking feature requires no studs for installation

